

# FastFrame

## Product



## Advantages

- Universal, accepts any filter with a header
- Simplifies filter change by eliminating clips and fasteners
- May be assembled into banks up to six frames high by any number wide
- Replaceable gasket creates leak free system integrity, ensuring that all of the air moving through the system will be treated by the filter
- Multiple stages of filters can be installed on each frame

**Typical applications:** Built-up bank frames for installation in HVAC applications in commercial, industrial, manufacturing and medical facilities.

**Construction:** 16-gauge galvanized steel frame with gasketed filter sealing flange, unique filter holding compression tabs accommodate any headered filter. May include multiple stages of filtration. Pre-drilled holes for bank assembly, marked top for ease of installation.

**Filters:** MERV 5 through 16. May also be used with adsorbent panels or modules.

**Additional data:** Available in stainless steel, consult factory.

See Literature 2429 for more details.

Model Number	Actual Depth (inches)	Actual Height (inches)	Actual Width (inches)	Weight (lbs.)
<b>For Built-up Bank Applications</b>				
M22001-004	2.69	24	12	4.3
M22001-002		20	20	4.9
M22001-007		24	20	5.4
M22001-001		24	24	56.0

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice. 2018-12-07